

IK

PROFESSIONAL PEST CONTROL SPRAYER

Stainless steel or metal professional sprayers



6 & 10 litre capacity


henchem
environmental management solutions

Cape Town
Unit 6b, Palmiet street, Stikland
(021) 948-7366

www.henchem.co.za

Durban
29 Eaton Road, Umbilo
061 473 0162

Gauteng
081 747 9932

* enquiries@henchem.co.za

IK INOX/SST professional sprayer



Sprayers manufactured in stainless steel having a 6 or 10 litre useful capacity

Sprayers especially manufactured with maximum resistance materials to be used with mineral and vegetable oils, curing agents and neutral cleaners. Can be similarly used with hydrocarbon based solvents, lubricants and petroleum derivatives. Not suitable for acids.

FEATURES:

- Seals and materials resistant to mineral and vegetable oils, curing agents and neutral cleaners.
- Innovative and ergonomic design.
- Stable base with feet brackets.
- Parking for easy use lance and serves as a handhold or holding bar when emptying the tank.
- Parking for the chamber during filling.
- Stainless steel lance and handle.
- Safety valve set at 6 bar.
- Standard compressed air connector in 6 or 10 l models.
- Pressure gauge.
- Wide funnel integrated into tank for easy filling.
- Adjustable cone nozzle and standard elbow with fan nozzle.
- Carrying straps for overs houlder transport.



MAIN ADVANTAGES:

- Option of working at pressures up to 6 bar.
- Greater range and possibility of spraying dense liquids.
- Option of spraying hot liquids.
- Superior resistance as regards solvents and petroleum derivatives.



Pressure regulator & Pressure release valve

Nozzle parking bay

INOX/SST:	6	10
• Total capacity litres:	9 L	13L
• Working capacity:	6 L	10L
• Litrel/min 6 Bar:	1,13 l/min	1.13l/min
• Gross weight:	4,4kg	4.9kg
• Net weight:	4kg	4.5kg
• Volume/ per unit:	0,036m2	0,036m2

IK METAL professional sprayer



Sprayers manufactured in metal having a 6 or 10 litre useful capacity

FEATURES

- Innovative and ergonomic design
- Stable base with feet brackets.
- Parking for easy use lance and serves as a handhold or holding bar when emptying the tank.
- Parking for the chamber during filling.
- Stainless steel handle and lance.
- Safety valve set at 6 bar
- Standard compressed air connector in 10 l models
- Pressure gauge
- Option of fitting a 50 cm extension tube.
- Wide funnel integrated into tank for easy filling.
- Adjustable cone nozzle and standard elbow with fan nozzle.
- Carrying straps for overshooulder transport

MAIN ADVANTAGES

- Option of working at pressures up to 6 bar.
- Greater range and possibility of spraying dense liquids.
- Option of spraying hot liquids
- Superior resistance as regards solvents and petroleum derivatives.

METAL	6	10
• Total capacity litres:	9 L	13L
• Working capacity:	6 L	10L
• Litre/min 6 Bar:	1,13 l/min	1.13l/min
• Gross weight:	4,8kg	5.2kg
• Net weight:	4,4kg	5.1kg
• Volume/ per unit:	0,036m2	0,036m2



Pressure regulator & Pressure release valve



Nozzle parking bay

HENCHEM – IK PROFESSIONAL SPRAYER